IN THE CLAIMS

Please cancel claims 4 and 11. Please amend claims 1, 2, 3, 5, 6, and 10 to read as follows:

1. (Currently Amended) <u>A M method for attaching solid hardwood</u> wood floor planks to a concrete floor surface comprises:

preparing, away from the site of installation, solid plank hardwood wood floorboards having a length of at least about 3 feet for attachment to said concrete floor surface;

applying <u>said floorboards</u> to said concrete floor surface with at least one water resistant, water impermeable adhesive in sufficient quantity to attach said <u>floor</u>boards to said surface;

placing the prepared solid plank hardwood said floorboards on the adhesive-coated concrete floor surface; and

allowing the adhesive to set.

- 2. (Currently Amended) A-The method of claim 1 wherein said preparing step include comprises providing said floorboards with surface wormholes/nailholes/scratches, colors and applying desired finishes, or a combination thereof. to said boards.
- 3. (Currently Amended) The method of claim 1 further comprising, before applying said adhesive to concrete floor surface, preparing said concrete floor surface to be clean, dry, smooth, low in surface moisture, and substantially flat.
- 4. (Canceled) The method of claim 1 further comprising using boards made of hardwood or soft wood of various species, having a length of at least about 3 feet.

B

- 5. (Currently Amended) A floor comprising a concrete floor surface with solid plank wood hardwood floor boards having a length of at least about 3 feet adhesively attached thereto, said adhesive being water resistant and water impermeable with no subflooring between said boards and said concrete floor
- 6. (Currently Amended) A-The floor of claim 5 comprising solid plank hardwood floor boards, -wherein said boards include including surface-formed wormholes/nail holes/scratches, colors and finishes, or a combination thereof.
- 7. (Original) The floor of claim 5 wherein said boards are of varying thicknesses.
- 8. (Original) The method of claim 1 further comprising, after said placing step, nailing said boards to said concrete floor surface through the adhesive layer.
- 9. (Original) The floor of claim 5 further comprising a plurality of nails that penetrate through said boards and into said concrete floor surface.
- 10. (Currently Amended) The method of claim 2 further comprising, before applying said adhesive to said surface, preparing said concrete floor surface to be clean, dry, smooth, low in surface moisture, and substantially flat.
 - 11. (Cancel)
- 12. (Original) The floor of claim 6 wherein said boards are of varying thicknesses.

Chi

surface.

Southern et al. Appl. No. 10/034,446 March 20, 2003



13. (Original) The method of claim 2 further comprising, after said placing step, nailing said boards to said concrete floor surface through the adhesive layer.